


TVIOD-PRM2EXIR28

2MP/1080p Prime HD TVI WDR EXIR Dome Camera w/2.8mm Lens

- 2.8mm Fixed Lens
- Up to 2MP HD resolution
- Up to 65 feet IR (infrared)
- IP66 Weatherproof



Megapixels:	2
Max Resolution:	1080p
Image Resolutions:	2MP (1928x 1088)
Image Sensor:	2MP CMOS Image Sensor
Min Illumination:	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
LEDs:	1
IR Distance:	65
OSD:	Yes
Operating Temperature	-40°F to +140°F, humidity 90% or less (non-condensing)
Dimension:	4.5in x 4.5in x 3.5in
Power:	DC12V±15%



TVIOD-PRM2EXIR28

HD1080P WDR EXIR Turret Camera

Specifications

Camera	
Image Sensor	2MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1928(H)*1088(V)
Min. illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25s to 1/50,000s
Lens	2.8mm
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0° - 360°; Tilt:0° - 75°; Rotate: 0° - 360°
Synchronization	Internal Synchronization
WDR	120dB
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	>62dB
Menu	
AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/ MWB
BLC	Support
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR
General	
Operating Conditions	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC ± 15%
Power Consumption	Max. 5W
Protection Level	IP66
IR Range	Up to 20m
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	91mm×82.6mm×68.3mm (4.5"×4.5"×3.5")
Weight	Approx. 450g (0.99208)

TVIOD-PRM2EXIR28

HD1080P WDR EXIR Turret Camera

Dimensions

