

TVIPTZ-PR1L23X

1.3MP 720P 23X True WDR Outdoor PTZ Camera

- 23X Optical Zoom
- 4-92.0mm lens
- HIKVISION_C UTC
- IP66 Weatherproof



Megapixels:	1.3
Max Resolution:	720p
Image Resolutions:	1.3MP (1288 x 720)
Image Sensor:	1/2.8inch Progressive Scan CMOS
Min Illumination:	Color: 0.05Lux@ (F1.4,AGC ON); B/W: 0.005Lux@ (F1.4,AGC ON)
LEDs:	N/A
IR Distance:	N/A
OSD:	Yes
Protocol:	Self-adaptive HIKVISION, Pelco-P, Pelco-D protocol
Operating Temperature	-22°F to +149°F, humidity 90% or less (non-condensing)
Dimension:	7.28in x 7.28in x 12.99in
Power:	24V AC
Pan Rotation:	360°endless
Tilt:	0°~90°(Auto Flip)
Touring:	8 patrols, up to 32 presets per patrol

TVIPTZ-PR1L23X

HD720P Turbo PTZ Dome Camera

Model	TVIPTZ-PR1L23X
Camera Module	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.05Lux@(F1.4,AGC ON); B/W: 0.005Lux@(F1.4,AGC ON)
Max. Image Resolution	1280x720
Focal Length	4-92.0mm, 23x
Digital Zoom	Not support
Zoom Speed	Approx.3s(Optical Wide~Tele)
Angle of View	49-2.2 degree(Wide~Tele)
Min. Working Distance	10~1,000mm(Wide~Tele)
Aperture Range	F1.4-F3.5
Focus Mode	Auto / Semiautomatic / Manual
DWDR	Support
S / N Ratio	≥ 50dB
Shutter Time	1-1/10,000s
AGC	Auto / Manual
White Balance	Auto / Manual / ATW / Indoor / Outdoor
Day & Night	IR Cut Filter
Privacy Mask	8 privacy masks programmable; a maximum of 4 zones can be masked simultaneously on the same video screen
Enhancement	3D DNR, BLC
Pan and Tilt	
Range	Pan:360° endless; Tilt: 0°~90°(Auto Flip)
Speed	Pan Manual Speed: 0.1°~160°/s, Pan Preset Speed: 160°/s Tilt Manual Speed: 0.1°~120°/s, Tilt Preset Speed: 120°/s
Number of Preset	256
Patrol	8 patrols, up to 32 presets per patrol
Pattern	4 patterns, with the total recording time not less than 10 minutes
Park Action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Panorama scan
Scheduled Task	Preset / Patrol / Pattern / Pan scan / Tilt scan / Panorama scan
RS-485 communication diagnosis	Support
Input/ Output	
Turbo HD Output	1 turbo HD720P/1080P output, 1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC
CVBS Output	1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC
Alarm Input	2
Alarm Output	1
RS-485 Interface	Half-duplex mode Self-adaptive HIKVISION, Pelco-P, Pelco-D protocol
UTC function	HIKVISION_C

TVIPTZ-PR1L23X

HD720P Turbo PTZ Dome Camera

General

Menu Language	English
Power	24VAC Outdoor dome: Max. 18W (Heater On), Max. 12W(Heater Off)
Working Temperature / Humidity	-30 °C-65°C(-22°F-149°F) 90% or less
Protection Level	IP66 standard TVS 4,000V lightning protection, surge protection and voltage transient protection
Mounting	Various mounting modes optional
Dimensions	Φ185×330mm (Φ7.28"×12.99")
Weight (approx.)	4Kg (8.81lbs)

Dimensions

