

TVIPTZ-PR2IRL23X

2MP Prime 23X Full HD HD-TVI IR PTZ Camera

- 1/3in Progressive Scan CMOS
- 2.8mm fixed lens
- Power using DC12V, PoE (802.3af)
- Micro SD, Max 64GB



Megapixels:	2
Image Resolutions:	1080P(1920× 1080)/720P(1280× 720)/D1(704× 576/704× 480)/ CIF(352× 288/352× 240)
Image Sensor:	1/3in CMOS
Min Illumination:	Color: 0.2Lux@ (F1.6,AGC ON) ; B / W: 0.02Lux@ (F1.6,AGC ON)
LEDs:	6
IR Distance:	393 feet
OSD:	Yes
Protocol:	Self-adaptive PELCO_C, HDCAM_C(need UTC controller)
Operating Temperature	-22°F - 140 °F, , Humidity 95% or less (non-condensing)
Dimension:	8.66in x 8.66in x 13.91in
Power:	24VAC
Pan Rotation:	360° endless
Tilt:	-15°-90° (Auto Flip)
Touring:	8 patrols, up to 32 presets per patrol




TVIPTZ-PR2IRL23X

1080P TVI IR PTZ Dome Camera

	TVIPTZ-PR2IRL23X
Camera	
Image Sensor	1 / 3" CMOS
Effective Pixel	3270K
Horizontal Resolution	1100TVL
Signal System	PAL / NTSC
Min. Illumination	Color: 0.2Lux@(F1.6,AGC ON) ; B / W: 0.02Lux@(F1.6,AGC ON)
White Balance	Auto / Manual / ATW / Indoor / Outdoor
AGC	Auto / Manual
S / N Ratio	≥50dB
3D DNR	Support
Digital WDR	Support
EIS	Support
Backlight Compensation	Support
Shutter Time	PAL: 1-1 / 10,000s ; NTSC: 1-1 / 10,000s
Day & Night	IR Cut Filter
Digital Zoom	16x
Privacy Mask	8 privacy masks programmable; a maximum of 8 zones can be masked simultaneously on the same video screen
Focus Model	Auto / Semiautomatic / Manual
Lens	
Focal Length	4-92mm, 23X
Zoom Speed	Approx.3.0s(Optical Wide-Tele)
Angle of View	49-2.2 degree(Wide-Tele)
Min. Working Distance	10-1500mm (Wide-Tele)
Aperture	F1.6-F3.7
Pan and Tilt	
Pan Range	360° endless
Pan Speed	Pan Manual Speed: 0.1°-160° / s; Pan Preset Speed: 240° / s
Tilt Range	-15°-90° (Auto Flip)
Tilt Speed	Tilt Manual Speed: 0.1°-120° / s; Tilt Preset Speed: 200° / s
Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples
Number of Preset	256
Patrol	8 patrols, up to 32 presets per patrol
Pattern	4 patterns, with the total recording time not less than 10 minutes
Power-off Memory	Support
Park Action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Frame Scan / Random scan / Panorama scan
PTZ Position Display	On / Off
Preset Freezing	Support
Scheduled Task	Preset / Patrol / Pattern / Pan scan / Tilt scan / Frame Scan / Random scan / Panorama scan
RS-485 communication diagnosis	Support
Infrared	
IR Distance	120m
IR Intensity	Automatically adjusted, depending on the zoom ratio
Input / Output	
Monitor Output	1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC
RS-485 Interface	Half-duplex mode; Self-adaptive HIKVISION, Pelco-P, Pelco-D protocol
UTC function	Self-adaptive PELCO_C, HDCAM_C(need UTC controller)
General	
Menu Language	English, Chinese
Power	24VAC
Working Temperature / Humidity	-30 °C-65°C(-22°F-149°F)(outdoor dome) 90% or less
Protection Level	IP66 standard (outdoor dome) TVS 4,000V lightning protection, surge protection and voltage transient protection
Mounting	Various mounting modes optional
Dimensions	φ220×353.4mm (φ8.66"×13.91")(Outdoor)
Weight (approx.)	5.5kg(12.13lbs)

Design and specifications are subject to change without notice.

Dimensions



Unit: mm