

TVIPTZ-SB2IR18XE

1080p Sibell TVI 2mp IR 18X indoor/outdoor PTZ

- TVI High Definition Over Coaxial Cable
- 2MP 1080P (1920 x 1080)
- 18X Optical Zoom
- 390 feet of IR night view



Megapixels:	2MP
Max Resolution:	1080p
Image Resolutions:	2MP (1920x1080) / 1.3M (1280x960) / 720P (1280x720) / D1 (704x576/704x480)
Image Sensor:	1/2.8" SONY CMOS Sensor 2.4MP
Min Illumination:	N/A
LEDs:	14
IR Distance:	390 feet
OSD:	Yes
Protocol:	Pelco-D, Pelco-P
Operating Temperature	Indoor: 32°~104°, Outdoor: -40°~140°
Dimension:	13in x 13in x 17in
Power:	DC12V/3A
Pan Rotation:	360°
Tilt:	93°
Touring:	4 groups

TVIPTZ-SB2IR18XE: Specifications

2mp TVI PTZ Weatherproof with Long range IR & 18x Optical Zoom



Key Features:

- 2 Mega Pixel 1080P (1920 x 1080)
- 18X Optical Zoom
- 390 feet of IR night view distance
- Programmable 360° Scan
- 220 Preset Points
- IP66 Weatherproof
- TVI High Definition Over Coaxial Cable
- 12vDC/3A Power Supply

Model#: TVIPTZ-SB2IR18XE	
Camera	
Image Sensor	1/2.8" SONY CMOS Sensor 2.4MP
Image Resolution	1080P
S/N Ratio	≥58dB
PTZ	
Horizontal Rotation Speed	60°/s
Horizontal Rotation Range	360°
Tilt Rotation Speed	360°
Tilt Rotation Range	93°
Auto Flip	Horizontal 180°, Vertical 93°
Ratio Speed	Support
360° Scan	User programmable
360° Scan Speed	01-64speed setting available
A-B Scan	User programmable
A-B Scan Speed	01-64speed setting available
PWR on Action	Memory/Tour/360 scan/AB scan/Home/Nop
Park Time	1-60 mins setting available
Dwell Preset	1-60s interval available
Preset Points	220
Go to Preset Speed	200°/s
Guard Tours	4 groups
Guard Points	Max.16 points, dwell time user selectable
Lens	
Focus Length	5.35mm-96.3mm
Focus Control	18X Optical Zoom
Night Vision	
Infrared LED	22x8PCS + 16x6PCS
IR Range	390 Feet (120m)
Auxiliary Interface	
Communication Protocol	Pelco-D, Pelco-P
Communication	RS485
Baud Rate	1200/2400/4800/9600bps
General	
Weatherproof	IP66
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Auto Control IR LED	PWM
OSD Menu	Yes English
Power	DC12V/3A
Power Consumption	≤ 36W
Lightning Protection	Transient voltage 6000V
Dimension	32x32x43(cm)
Weight	7kgs
Operating Temperature	Indoor: 32°~104°, Outdoor: -40°~140°