

TVIVD-PR2IR

2MP Turbo HD Prime 1080P Vandal Proof IR Turret Dome Camera

- 3.6mm Lens @ F1.2
- 2MP high performance CMOS
- IK10 Impact Protection
- EXIR technology, up to 20M IR



Megapixels:	2
Max Resolution:	1080p
Image Resolutions:	1080P(1920× 1080)/720P(1280× 720)/D1(704× 576/704× 480)/ CIF(352× 288/352× 240)
Image Sensor:	2MP CMOS Image Sensor
Min Illumination:	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
LEDs:	2
IR Distance:	65 feet
OSD:	Yes
Protocol:	N/A
Operating Temperature	-40 °F – 140 °F, Humidity 90% or less (non-condensing)
Dimension:	4.43in x 4.43in x 3.25in
Power:	12V DC±15%



TVIVD-PR2IR

HD1080P WDR Vandal Proof EXIR Dome Camera

Specifications

Camera	
Image Sensor	2MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1928(H)*1088(V)
Min. illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25s to 1/50,000s
Lens	3.6mm @ F1.2
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0° - 340°; Tilt:0° - 75°; Rotate: 0° - 355°
Synchronization	Internal Synchronization
WDR	120dB
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	>62dB
Menu	
AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/ MWB
BLC	Support
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR
General	
Operating Conditions	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC ± 15%
Power Consumption	Max. 5W
Protection Level	IP66
IR Range	Up to 20m
Impact Protection	IK10
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	φ111mm×82.5mm (φ4.43"×3.25")
Weight	Approx. 350g (0.77lb)

Dimensions

