

TVIVD-PR2IR28

2MP Turbo HD Turret WDR 1080P Vandal Proof IR Dome Camera

- Up to 2 megapixel (1920 × 1080) resolution
- 2.8mm Fixed lens
- 98 feet IR (infrared) range
- IK10 Impact rating



Megapixels:	2
Max Resolution:	1080p
Image Resolutions:	2MP (1920x1080) / 1.3M (1280x960) / 720P (1280x720) / D1 (704x576/704x480)
Image Sensor:	2MP CMOS Image Sensor
Min Illumination:	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
LEDs:	N/A
IR Distance:	98 feet
OSD:	Yes
Operating Temperature	40 °F – 140 °F, Humidity 90% or less (non-condensing)
Dimension:	4.43in x 4.43in x 3.25in
Power:	12 VDC$\hat{A}$±15%



HD1080P WDR Vandal Proof EXIR Dome Camera

Camera	
Image Sensor	2MP CMOS Image Sensor
Signal System	PAL/NTSC
Effective Pixels	1928(H)*1088(V)
Min. illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25s to 1/50,000s
Lens	2.8mm @ F1.2
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0° - 340°; Tilt:0° - 75°; Rotate: 0° - 355°
Synchronization	Internal Synchronization
WDR	120dB
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	> 62dB
Menu	
AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW/ MWB
BLC	Support
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR
General	
Operating Conditions	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC± 15%
Power Consumption	Max. 5W
Protection Level	IP66
IR Range	Up to 20m
Impact Protection	IK10
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	φ111mm×82.5mm (φ4.43″×3.25″)
Weight	Approx. 350g (0.77lb)

Unit: m m