

TVIVD-PR5EXIR28

5MP Prime HD TVI Indoor/Outdoor EXIR Vandal Dome Camera

- 2.8mm Fixed Lens
- IP67 ingress protection
- Up to 65 feet IR with EXIR
- IK10 Vandal Proof



Megapixels:	5MP
Max Resolution:	5MP (2592 x 1944)
Image Resolutions:	5MP (2592 x 1944) / 4MP (2560 x 1440)
Image Sensor:	5 MP CMOS image sensor
Min Illumination:	Color: 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
LEDs:	2
IR Distance:	65 feet
OSD:	N/A
Operating Temperature	-40°F to +140°F, 10 % ~ 90 %relative humidity
Dimension:	3.58in x 3.58in x 2.69in
Power:	DC12V (± 20%)



TVIVD-PR5EXIR28

5MP Prime HD TVI Indoor/Outdoor EXIR Vandal Dome Camera

Specifications

Camera	
Image Sensor	5 MP CMOS image sensor
Effective Pixels	2592(H) × 1944(V)
Min. illumination	Color: 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	PAL: 1/25s to 1/50,000s NTSC: 1/30 s to 1/50,000s
Lens	2.8mm
Horizontal Field of View	102°
Lens Mount	Φ14
Day & Night	ICR
Angle Adjustment	Pan: 0° to 340°; Tilt: 0° to 75°; Rotate: 0° to 355°
Synchronization	Internal synchronization
Video Frame Rate	5MP @20 fps and 4MP @30fps
HD Video Output	1 HD analog output
Menu	
AGC	Support
D/N Mode	Auto/Color/BW(Black and White)
White Balance	ATW/MWB
BLC	Support
Language	English, Chinese
Functions	Brightness, Sharpness, Digital noise reduction, Mirror, Bad pixel correction, Smart IR
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 20%
Power Consumption	Max. 7.5W
Protection Level	IP67, IK10
IR Range	Up to 20m
Communication	Up the coax, Protocol: HIKVISION-C(TVI output)
Dimensions	3.58" × 2.69"
Weight	Approx. 2 lb.